



### Bare Seamless

Wire Size	Stud Size	Copper Nickel Plated
22-18		10083LNP
16-14		10173XLNP
12-10		10313LNP



### Bare Brazed Rings

Wire Size	Stud Size	Copper Nickel Plated
16-14	10	10100BZNP
12-10	8	10220BZNP
12-10	10	10230BZNP
12-10	1/4	10240BZNP



### Bare Butted

22-18	10080NP
16-14	10170NP
12-10	10310NP



Non-Insulated butted, seamless and brazed seam parts are made of copper. They are nickel plated for temperatures up to 650° F (343° C).

## Piggyback Connectors

### Bare Butted Seam

Wire Size	Tab Width	Part No.
22-18	.250 x .032	10662
16-14	.250 x .032	10663
12-10	.250 x .032	10666



### Vinyl Insulated

22-18	.250 x .032	20662#
16-14	.250 x .032	20663#
12-10	.250 x .032	20664#



### Nylon Insulated

22-18	.250 x .032	20662N#
16-14	.250 x .032	20663N#
12-10	.250 x .032	20664N#



### 3-Pc Nylon w/ Sleeve

Wire Size	Tab Width	Part No.
22-18	.250 x .032	30662#
16-14	.250 x .032	30663#
12-10	.250 x .032	30664#



### 3-Pc Nylon Fully Insulated

22-18	.250 x .032	32662#
16-14	.250 x .032	32663#
3 PC. TOOL		20717



### Heat Shrink

Wire Size	Stud Size	Polyolefin Part No.	NYAX
22-18	.250 x .032	40662	70662
16-14	.250 x .032	40663	70663
12-10	.250 x .032	40664	70664

