












## Finger Grip Connectors

Rated to 105°C (221°F) 600 volt max

Wire Size	Min.	Max	Part No.	
18-10	2 #18	3 #12	20584*	
18-8	3 #16	5 #12	20586*	
18-8	3 #14 w/1 #18	3 #10	20588*	
14-6	2 #10 w/1 #12	1 #8 w/3 #10	20589*	
For a wider range of coverage				
22-8	3 #22	4 #12	20509*	




## Screw On Connectors

Rated 105°C (221°F) 300/600 Volt Max.

Wire Size	Min.	Max	Part No.	
22-14	2 #22	1 #16 w/1 #18	20501#	
22-14	2 #22	3 #16	20502#	
22-14	1 #18 w/ 1 #20	4 #16 w/ 1 #20	20503#	
22-10	3 #20	2 #12 w/ 2 #14	20504#	
22-10	3 #18	2 #20 w/2 #12	20506#	


## Performance Plus Connectors

Rated 105°C (221°F) 300/600 Volt Max.  
 Replaces eight standard connectors

22-12	2 #22	2 #12	20540*	
18-8	2 #18	2 #8	20541*	
14-8	4 #14	5 #12	20542*	

## Ceramic Connectors

Rated 1000°F Max. 600 V

22-14	1 #14 w/ 1 #16	2 #14	20543	
22-10	3 #14	2 #10	20544	
18-8	3 #14 w/ 3 #16	2 #8	20545	

## Winged Grounding Connector

Color coded GREEN for quick identification as a grounding conductor for copper wire only.  
 Rated to 105°C (221°F) 1000 volt max

14-10	2 #14	5 #12	20583*	
-------	-------	-------	--------	---

## IDC Connectors - Gel Filled

P/N	Photo	Wire Gauge	Max OD	How to use
20528 Yellow		(22-26 AWG)	1.52mm	
20527 Orange		(18-26AWG)	2.08mm	
20526 Red		(19-26AWG)	1.67mm	
20525 Red		(19-26AWG)	2.08mm	

## W/P Connector Kits

Part No.: 5990-34  
 34 pc. Aqua W/P Connector Kit  
 20580\* - 20 pc.  
 20581\* - 10 pc.  
 20582\* - 4 pc.

### Purchase Individually

20580 22-12 Orange W/P Connector  
 20581 22-8 Red W/P Connector  
 20582 14-6 Blue W/P Connector

