

Non-Insulated Butted Seam Terminals are made of steel. They are nickel plated for temperatures up to 900° F (482° C)



## Rings

Wire Size	Tab Width	Steel Nickel Plated
22-18	6 Slim	10021HT
	6	10020HT
	8	10030HT
	8	10038HT
	10	10040HT
	1/4	10041HT
	5/16	10042HT
3/8	10043HT	
16-14	6 Slim	10085HT
	6	10086HT
	8	10090HT
	10	10100HT
	1/4 Slim	10114HT
	1/4	10101HT
	5/16	10102HT
	3/8	10103HT
12-10	6	10210HT
	8	10220HT
	10	10230HT
	1/4 Slim	10245HT
	1/4	10240HT
	5/16	10250HT
8	10	10610HT
	1/4	10611HT
	5/16	10612HT
	3/8	10613HT
6	10	10615HT
	1/4	10616HT
	5/16	10617HT
	3/8	10618HT
4	5/16	10621HT
	3/8	10622HT
2	1/4	10628HT
	5/16	10629HT
	3/8	10630HT

## Butt Connectors

22-18	10080HT
16-14	10170HT
12-10	10310HT

## Quick Connects

Wire Size	Tab Width	Steel Nickel Plated
22-18	.250 x .032 Female	10176HT
	.250 x .032 Male	10177HT
	.187 x .020 Female	10192HT
16-14	.187 x .020 Female	10195HT
	.250 x .032 Female	10180HT
	.250 x .032 Male	10181HT
12-10	.250 x .032 Female	10187HT
	.250 x .032 Male	10186HT

## Spades

22-18	6	10050HT
	8	10060HT
	10	10070HT
16-14	6	10140HT
	8	10150HT
	10	10160HT
12-10	6	10270HT
	8	10280HT
	10	10290HT
	1/4	10234HT

## Block Spade

16-14	8	10152HT
12-10	10	10292HT

## Flags

16-14	.250 Female	10189HT
-------	-------------	---------

High Temperature Terminals

**UP TO  
650°F**

### Bare Seamless

Wire Size	Stud Size	Copper Nickel Plated
22-18		10083LNP
16-14		10173XLNP
12-10		10313LNP



### Bare Brazed Rings

Wire Size	Stud Size	Copper Nickel Plated
16-14	10	10100BZNP
12-10	8	10220BZNP
12-10	10	10230BZNP
12-10	1/4	10240BZNP



### Bare Butted

22-18		10080NP
16-14		10170NP
12-10		10310NP



Non-Insulated butted, seamless and brazed seam parts are made of copper. They are nickel plated for temperatures up to 650° F (343° C).

## Piggyback Connectors

### Bare Butted Seam

Wire Size	Tab Width	Part No.
22-18	.250 x .032	10662
16-14	.250 x .032	10663
12-10	.250 x .032	10666



### 3-Pc Nylon w/ Sleeve

Wire Size	Tab Width	Part No.
22-18	.250 x .032	30662#
16-14	.250 x .032	30663#
12-10	.250 x .032	30664#



### Vinyl Insulated

22-18	.250 x .032	20662#
16-14	.250 x .032	20663#
12-10	.250 x .032	20664#



### 3-Pc Nylon Fully Insulated

22-18	.250 x .032	32662#
16-14	.250 x .032	32663#
3 PC. TOOL		20717



### Nylon Insulated

22-18	.250 x .032	20662N#
16-14	.250 x .032	20663N#
12-10	.250 x .032	20664N#



### Heat Shrink

Wire Size	Stud Size	Polyolefin Part No.	NYAX
22-18	.250 x .032	40662	70662
16-14	.250 x .032	40663	70663
12-10	.250 x .032	40664	70664

