











Finger Grip Connectors

Rated to 105°C (221°F) 600 volt max

Wire Size	Min.	Max	Part No.	
18-10	2 #18	3 #12	20584*	
18-8	3 #16	5 #12	20586*	
18-8	3 #14 w/1 #18	3 #10	20588*	
14-6	2 #10 w/1 #12	1 #8 w/3 #10	20589*	
For a wider range of coverage				
22-8	3 #22	4 #12	20509*	



Screw On Connectors

Rated 105°C (221°F) 300/600 Volt Max.

Wire Size	Min.	Max	Part No.	
22-14	2 #22	1 #16 w/1 #18	20501#	
22-14	2 #22	3 #16	20502#	
22-14	1 #18 w/ 1 #20	4 #16 w/ 1 #20	20503#	
22-10	3 #20	2 #12 w/ 2 #14	20504#	
22-10	3 #18	2 #20 w/2 #12	20506#	


Performance Plus Connectors

Rated 105°C (221°F) 300/600 Volt Max.
 Replaces eight standard connectors

22-12	2 #22	2 #12	20540*	
18-8	2 #18	2 #8	20541*	
14-8	4 #14	5 #12	20542*	

Ceramic Connectors

Rated 1000°F Max. 600 V


22-14	1 #14 w/ 1 #16	2 #14	20543	
22-10	3 #14	2 #10	20544	
18-8	3 #14 w/ 3 #16	2 #8	20545	

Winged Grounding Connector

Color coded GREEN for quick identification as a grounding conductor for copper wire only.
 Rated to 105°C (221°F) 1000 volt max

14-10	2 #14	5 #12	20583*	
-------	-------	-------	--------	---

IDC Connectors - Gel Filled

P/N	Photo	Wire Gauge	Max OD	How to use
20528 Yellow		(22-26 AWG)	1.52mm	
20527 Orange		(18-26AWG)	2.08mm	
20526 Red		(19-26AWG)	1.67mm	
20525 Red		(19-26AWG)	2.08mm	

W/P Connector Kits

Part No.: 5990-34
 34 pc. Aqua W/P Connector Kit
 20580* - 20 pc.
 20581* - 10 pc.
 20582* - 4 pc.

Purchase Individually

20580 22-12 Orange W/P Connector
 20581 22-8 Red W/P Connector
 20582 14-6 Blue W/P Connector





Rated 105°C 600 volts

75°C 300 volts


20510
 #20510UL import
 22-18 with stop

20500
 #20500J import
 18-14 with stop

20512
 #20512UL import
 18-14 no stop

20511
 #20511UL
 12-10 with stop

Flame Retardant
 #20517 no stop
 #20529 with stop
 18-14



Made in U.S.A

T-Tap Connectors



Rated 105°C 600 volts

Rated 105°C 600 volts

20513
 24-20

20514
 #20514UL
 22-16

20515
 #20515UL
 16-14

20516K
 #20516UL
 12-10

20514DB#
 22-16

20515DB#
 16-14

20516DB#
 12-10



IDC Connectors

Misc. Connectors

Wire Size	Description	Part No.
22-14	Blue w/ Gel 3M 314 IMP	20518* 20518A#
22-14	Clear 3M 314U	20519+
22-16	Black w/Gel 3M 316IR	20520#

Wire Size	Description	Part No.
18-14 / 12-10	Brown Dual Tap 3M 902 IMP	20521* 20521A#
22-16 / 12-10	Red Dual Tap 3M 558 IMP	20555+ 20555A#
18-16	Blue Tap w/ Gel 3M 804 IMP	20522+ 20522A#
18-16	Bullet Style Tap .157 Male 3M 901 IMP	20523+ 20523A#
18-16	Auto Fuse Holder 3M 972 IMP	20524 20524A#