

Specification Details

PARTS PER UNIT	1 (25FT)
FEATURES	COPPER CONDUCTOR FOR MAXIMUM CONDUCTIVITY, INSULATION IS FLAME-RETARDANT, MEETS OR EXCEEDS SAE J1127, SGT TYPE, PVC INSULATION RESISTS ABRASION, FUEL, OIL, ACID &ND SALT
APPLICATION	AUTOMOTIVE, COMMERCIAL, INDUSTRIAL, TRUCK
GAUGE	4
CONDUCTOR MATERIAL	COPPER
CABLE NOMINAL OUTER DIAMETER	0.36IN
INSULATION MATERIAL	PVC
INSULATION THICKNESS	0.045 IN
PACK TYPE	ROLL
PROP 65 ITEM	DEHP, DINP
SAE	J1127
STRAND COUNT	70
STRAND GAUGE	23
SUBJECT TO PROP 65	YES
TEMPERATURE RANGE (°C)	-50 TO 105°C
TEMPERATURE RANGE (°F)	-58 TO 221°F
UL / CSA	NO
VOLTAGE	60 V
WORKS WITH BRAND	COPPER CONNECTORS NOT BRANDED
CABLE NOMINAL OUTER DIAMETER	0.36 IN
COLOR	RED
PRODUCT LENGTH	10.25 IN, 12.00 IN
PRODUCT WIDTH	1.62 IN, 10.25 IN, 12.00 IN
ROHS COMPLIANT	YES
SKU	58004-25RD
CABLE LENGTH	25 FT
PRODUCT WEIGHT	
COUNTRY OF ORIGIN	USA