

# Pin Terminals

## Vinyl Insulated

Wire Size    Part Number

22-18    PTV1



16-14    PTV2



12-10    PTV5



## 2-Pc Nylon

Wire Size    Part Number

22-18    PTN1 **NEW**



16-14    PTN2 **NEW**



12-10    PTN5 **NEW**



## 3-Pc Nylon w/ Sleeve

Wire Size    Part Number

22-18    PT3N1



16-14    PT3N2



12-10    PT3N5



# Flags

## Non Insulated

Wire Size    Part Number    Tab Width

22-18    12188    .187 **NEW**  
10188    .250



16-14    12189    .187 **NEW**  
10189    .250  
10669 (male) .250



12-10    10190    .250



## Heat Shrink

Wire Size    Part Number    Tab Width

22-18    42188    .187 **NEW**  
40188    .250



16-14    42189    .187 **NEW**  
40189    .250



12-10    40190    .250



## Nylon Insulated

22-18    22188    .187 **NEW**  
20188    .250



16-14    22189    .187 **NEW**  
20189    .250



12-10    20190    .250



See Page 37 [Tool \(20594\)](#) for 22-18 and 16-14 and [Tool \(20704\)](#) for 16-14 and 12-10.

## VOLTAGE RATINGS

Insulated Copper Terminals  
Insulated Brass Disconnects  
Tap Splices (16-10AWG)  
Tap Splices (18AWG)

600 volts MAX  
300 volts MAX  
32 volts MAX  
18 volts MAX