

# Heat Shrink Terminals

Crimp & Seal (A)



Solder & Seal (B)



Crimp, Solder & Seal (C)



Crimp & Seal (A)

Solder & Seal (B)

Crimp, Solder & Seal (C)

The terminals are copper (.110 alloy). The tubing is a high quality polyolefin. Seamless connectors used on butts. Multiple wall heat shrinkable tubing, clearly marked. Rings and spades are brazed seam. Color coded with wire size.

Description	Wire Size	Stud/Tab Width	Crimp & Seal (A)	Solder & Seal (B)	Crimp, Solder & Seal (C)	NYAX Crimp & Seal (A)
Butts	24-20		40024	60024	80024	
	22-18		20082	60082	80082	40082
	16-14		20172	60172	80172	40172
	12-10		20312	60312	80312	40312
Rings	22-18	6	40020	60020	80020	70020
		8	40030	60030	80030	70030
		10	40040	60040	80040	70040
		1/4	40041	60041	80041	70041
		5/16	40042	60042	80042	70042
		3/8	40043	60043	80043	70043
	16-14	8	40090	60090	80090	70090
		10	40100	60100	80100	70100
		1/4	40101	60101	80101	70101
		5/16	40102	60102	80102	70102
		3/8	40103	60103	80103	70103
	12-10	10	40230	60230	80230	70230
		1/4	40240	60240	80240	70240
		5/16	40250	60250	80250	70250
3/8		40260	60260	80260	70260	
1/2		40233	60233	80233	70233	
Spade	22-18	10	40070	60070	80070	70070
	16-14	10	40160	60160	80160	70160
	12-10	10	40290	60290	80290	70290
Quick Disconnects	22-18	.250 Fem.	40176	60176	80176	70176
		.250 Male	40177	60177	80177	70177
	16-14	.250 Fem.	40180	60180	80180	70180
		.250 Male	40181	60181	80181	70181
	12-10	.250 Fem.	40187	60187	80187	70187
		.250 Male	40186	60186	80186	70186
Fully Insulated QDC	22-18	.250 Fem.	40207	60179	80179	70207
	16-14	.250 Fem.	40209	60183	80183	70209
	12-10	.250 Fem.	40213	60199	80199	70213
<b>Heat Shrink Fully Insulated Female Disconnects</b>						

Brass support sleeve for improved pull-out force resistance.



Fully Insulated QDC	16-14	.250 Fem.	40180BRS
	12-10	.250 Fem.	40187BRS

