



**100ft
ROLL**

Primary Wire

	8 GA	10 GA	12 GA	14 GA	16 GA	18 GA	20 GA
Purple		54100	54120	54140	54160	54180	
Black	54081	54101	54121	54141	54161	54181	54201
Orange		54102	54122	54142	54162	54182	
Green		54103	54123	54143	54163	54183	
White	54084	54104	54124	54144	54164	54184	
Brown		54105	54125	54145	54165	54185	
Pink		54106	54126	54146	54166	54186	
Red	54087	54107	54127	54147	54167	54187	54207
Blue		54108	54128	54148	54168	54188	
Yellow		54109	54129	54149	54169	54189	
Gray		541010	541210	541410	541610	541810	


80°C 60 Volt PVC Insulation

Recommended Uses

- 10 GA For generator, heater switch, air conditioner, meter & panel lights
- 12 GA Light switches & ignition switches
- 14 GA Horn button circuit, head lights, gas gauge to coil & cigarette lighter
- 16 GA Header leads, gas gauge, directionals, stop signal & generator to starter
- 18 GA Single, bulb, low amp circuits & clock

Trailer Wire

Wire Size	2 Conductor Black-Red
14	53142
16	53162
18	53182




Jacketed Primary Wire

Wire Size	2 Conductor Black-White
8	55082
10	55102
12	55122
14	55142
16	55162



Trailer Wire

Wire Size	3 Conductor Brown-Green-Yellow
14	53143
16	53163
18	53183




Jacketed Primary Wire

Wire Size	3 Conductor Black-Green-White
10	55103
12	55123
14	55143
16	55163




Trailer Wire

Wire Size	4 Conductor Brown-Green Yellow-White
14	53144
16	53164
18	53184



Jacketed Primary Wire

Wire Size	4 Conductor Black-Green Red-White
10	55104
12	55124
14	55144
16	55164



Recommended for RVs, boats and utility trailers.

Recommended for auto, truck, agriculture, construction and light marine applications. Heavy Duty flat PVC outer jacket is abrasion resistant and protects against moisture, oil, acid & salt.