

Screw on Connectors

Finger Grip Connectors

Rated to 105°C (221°F) 600 volt max

Wire Size	Min.	Max	Part Number
18-10	2 #18	3 #12	20584
18-8	3 #16	5 #12	20586
18-8	3 #14 w/1 #18	3 #10	20588
14-6	2 #10 w/1 #12	1 #8 w/3 #10	20589
<i>For a wider range of coverage</i>			
22-8	3 #22	4 #12	20509



Screw On Connectors

Rated 105°C (221°F) 300/600 Volt Max.

Wire Size	Min.	Max	Part Number
22-14	2 #22	1 #16 w/1 #18	20501
22-14	2 #22	3 #16	20502
22-14	1 #18 w/ 1 #20	4 #16 w/ 1 #20	20503
22-10	3 #20	2 #12 w/ 2 #14	20504
22-10	3 #18	2 #20 w/2 #12	20506



Performance Plus Connectors

Rated 105°C (221°F) 300/600 Volt Max.
Replaces eight standard connectors

22-12	2 #22	2 #12	20540
18-8	2 #18	2 #8	20541
14-8	4 #14	5 #12	20542



Ceramic Connectors

Rated 1000°F Max. 600 V

22-14	1 #14 w/ 1 #16	2 #14	20543
22-10	3 #14	2 #10	20544
18-8	3 #14 w/ 3 #16	2 #8	20545



Winged Grounding Connector

Color coded GREEN for quick identification as a grounding conductor for copper wire only.
Rated to 105°C (221°F) 1000 volt max

14-10	2 #14	5 #12	20583
-------	-------	-------	-------

