

# Female Quick Disconnects

## Bare Butted Seam

Wire Size	Tab Width	Part Number
22-18	.110 x .020	10191
	.187 x .020	10192
	.205 x .020	10193
	.250 x .032	10176

16-14	.110 x .020	10194
	.187 x .020	10195
	.205 x .020	10196
	.250 x .032	10180

12-10	.250 x .032	10187
	.375 x .032	10166



## 3-Pc Nylon w/ Sleeve

Wire Size	Tab Width	Part Number
22-18	.110 x .020	30191
	.187 x .020	30192
	.250 x .032	30176

16-14	.110 x .020	30194
	.187 x .020	30195
	.250 x .032	30180
	.375 x .032	30375

12-10	.187 x .032	30167
	.250 x .032	30187
	.375 x .032	30166
	Larger Barrel .250 x .032	30187B



## Vinyl Insulated

22-18	.110 x .020	20191
	.187 x .020	20192
	.187 x .020	50192
	.205 x .020	20193
	.205 x .020	50193

16-14	.110 x .020	20194
	.187 x .020	20195
	.187 x .020	50195
	.205 x .020	20196
	.205 x .020	50196
	.250 x .032	50180

12-10	.187 x .032	20167
	.250 x .032	50187
	.375 x .032	20166
	Larger Barrel .250 X .032	50187B



## Heat Shrink

22-18	.110 x .020	40191
	.187 x .020	40192
	.250 x .032	40176

16-14	.110 x .020	40194
	.187 x .020	40195
	.250 x .032	40180
	.250 x .032	40180BRS (Brass Sleeve)

12-10	.250 x .032	40187
	.250 x .032	40187BRS (Brass Sleeve)
	.375 x .032	40166



## Nylon Insulated

22-18	.187 x .020	50192N
	.205 x .020	50193N
	.250 x .032	50176N

16-14	.187 x .020	20195N
	.187 x .020	50195N
	.205 x .020	50196N
	.250 x .032	50180N
	.375 x .032	20375N
		NEW

12-10	.187 x .032	20167N
	.250 x .032	50187N Rolled
	.375 x .032	20166N
	.250 x .032	50213N Folded



The part numbers beginning in "2" are Extruded Vinyl.

The parts numbers beginning in "5" are Injection Molded with funnel entry.