

The MCTM-101 and MTCM-102



Our mylar tape fed products are universally spaced and can be applied with the MTCM - 101 and other standard electric applications.

The MCTM - 101 and MCTM - 102 are heavy duty, durable and simple to operate. Powered by 85-100 PSI air pressure and 110 VAC. Fully automatic and foot actuated.

The MCTM - 101 machine comes with three sets of dies. One set for each size: 22-18, 16-14 and 12-10 gauge. Each die crimps bare, vinyl, and heat shrink.

The MCTM - 102 machine comes with two sets of dies. One set for each size: 8 and 6 gauge. Each die crimps bare and vinyl up to 6 gauge.

Machine Specifications:



- Most rings, spades and butt connectors can be ordered by adding "MT" as a suffix. Call customer service with questions.

Weight 70 Lbs.
 Air: 1/4" NPT Inlet
 Stroke Rate: 1000 SPH
 Foot Pedal: Momentary switch. 5ft. cord
 Dimensions: 12" Wide - 20" Deep - 17"
 Height Electrical: 110V 5 ft. grounded standard plug
 Reel Size: 14" outside dia reel with 3/4" core
 Built in counter
 Operates with PLC programmable controller
 Buzzer to alert operator of machine malfunction
 Index feature for single or double spaced terminals

Vinyl Electrical Tape



Length	Description	Part #	Length	Description	Part #
3/4 x 60'	Black 7 mil	TAPE-BK	3/4 x 60'	White 7 mil	TAPE-WH
3/4 x 60'	Blue 7 mil	TAPE-BL	3/4 x 60'	Yellow 7 mil	TAPE-YL
3/4 x 60'	Green 7 mil	TAPE-GN	3/4 x 60'	Brown 7 mil	TAPE-BR
3/4 x 60'	Orange 7 mil	TAPE-OR	3/4 x 66'	3M Super 33 7 mil	TAPE-33
3/4 x 60'	Red 7 mil	TAPE-RD	3/4 x 66'	3M Super 88 8.5 mil	TAPE-88

Wire Processing

Call about our wire processing capabilities. We have added cutting and stripping abilities to go along with the crimp machine. Let us cut and strip your wires, cutting to length, full or partial strip and window stripping available for low runs. Simple harnesses, using Hillsdale connectors can now be done in house.

