

Bare Butted Seam

| Wire Size | Stud Size | Part Number |
|-----------|-----------|-------------|
|-----------|-----------|-------------|

| | | |
|-------|--------|---------|
| 22-18 | 6-8-10 | 10040M* |
|-------|--------|---------|

| | | |
|-------|--------|---------|
| 16-14 | 6-8-10 | 10100M* |
|-------|--------|---------|

| | | |
|-------|--------|---------|
| 12-10 | 6-8-10 | 10230M* |
|-------|--------|---------|



Nylon Insulated

| Wire Size | Stud Size | Part Number |
|-----------|-----------|-------------|
|-----------|-----------|-------------|

| | | |
|-------|--------|----------|
| 22-18 | 6-8-10 | 50040MN* |
|-------|--------|----------|

| | | |
|-------|--------|----------|
| 16-14 | 6-8-10 | 50100MN* |
|-------|--------|----------|

| | | |
|-------|--------|----------|
| 12-10 | 6-8-10 | 50230MN* |
|-------|--------|----------|



Bare Brazed Seam

| | | |
|-------|--------|-----------|
| 22-18 | 6-8-10 | 10040MBZ* |
|-------|--------|-----------|

| | | |
|-------|--------|-----------|
| 16-14 | 6-8-10 | 10100MBZ* |
|-------|--------|-----------|

| | | |
|-------|--------|-----------|
| 12-10 | 6-8-10 | 10230MBZ* |
|-------|--------|-----------|



3-Pc Nylon w/ Sleeve

| | | |
|-------|--------|--------|
| 22-18 | 6-8-10 | 30040M |
|-------|--------|--------|

| | | |
|-------|--------|--------|
| 16-14 | 6-8-10 | 30100M |
|-------|--------|--------|

| | | |
|-------|--------|--------|
| 12-10 | 6-8-10 | 30230M |
|-------|--------|--------|



Vinyl Insulated

| | | |
|-------|--------|---------|
| 22-18 | 6-8-10 | 50040M* |
|-------|--------|---------|

| | | |
|-------|--------|---------|
| 16-14 | 6-8-10 | 50100M* |
|-------|--------|---------|

| | | |
|-------|--------|---------|
| 12-10 | 6-8-10 | 50230M* |
|-------|--------|---------|



Heat Shrink

| | | |
|-------|--------|--------|
| 22-18 | 6-8-10 | 40040M |
|-------|--------|--------|

| | | |
|-------|--------|--------|
| 16-14 | 6-8-10 | 40100M |
|-------|--------|--------|

| | | |
|-------|--------|--------|
| 12-10 | 6-8-10 | 40230M |
|-------|--------|--------|



Star Rings

Blades can pierce surfaces to ensure a good connection



Vinyl Insulated

| Wire Size | Stud Size | Part Number |
|-----------|-----------|-------------|
|-----------|-----------|-------------|

| | | |
|-------|--------|----------------|
| 22-18 | 6 8 | 50301 50302 |
|-------|--------|----------------|

| | | |
|-------|---------|----------------|
| 16-14 | 8 10 | 50305 50306 |
|-------|---------|----------------|



| WIRE SIZE CROSS REFERENCE | |
|---------------------------|-------|
| Metric mm ² | AWG |
| 0.5 | 26-22 |
| 1.25 | 22-16 |
| 2.0 | 16-14 |
| 5.5 | 12-10 |
| 8.0 | 8 |
| 14.0 | 6 |
| 22.0 | 4 |
| 35.0 | 2 |
| 60.0 | 1/0 |
| 70.0 | 2/0 |
| 80.0 | 3/0 |
| 100.0 | 4/0 |